SAFETY DATA SHEET **Tableau Spot Remover**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name

Tableau Spot Remover

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

PC35 Washing and cleaning products

1.3. Details of the supplier of the safety data sheet

Supplier

RPM Marketing (Sussex)

PO Box 1

BEXHILL ON SEA East Sussex **TN39 3ZQ** 01424 224620

info@tableauproducts.com

1.4. Emergency telephone number

Emergency telephone

01424 575131 Ext 6 Office Hours (Mon- Fri 9am-5pm) only.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC/1272/2008)

Physical hazards

Aerosol 1 - H222, H229

Health hazards

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards

Aquatic Chronic 2 - H411

1999/45/EC)

Classification (67/548/EEC or Xi;R36/38. F+;R12. N;R51/53. R67.

Human health

Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this

container is dangerous and can be fatal.

Environmental

The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent

material the aerosol vapours can be ignited.

2.2. Label elements

Pictogram







Signal word

Danger

Tableau Spot Remover

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P102 Keep out of reach of children.

P501 Dispose of contents/ container in accordance with local regulations.

P260 Do not breathe vapour/ spray.

P262 Do not get in eyes, on skin, or on clothing.

Contains Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, PROPAN-2-OL, ETHYL ACETATE

Detergent labelling ≥ 30% aliphatic hydrocarbons

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

30-60%

Classification

Flam. Gas 1 - H220

Classification (67/548/EEC or 1999/45/EC)

F+;R12 Carc. Cat. 1;R45 Muta. Cat. 2;R46

Press. Gas, Liquefied - H280

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

30-60%

CAS number: 64742-49-0 EC number: 927-510-4 REACH registration number: 01-

2119475515-33

Classification

Classification (67/548/EEC or 1999/45/EC)

Xn;R65. Xi;R38. F;R11. N;R51/53.

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315

STOT SE 3 - H336

Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

Tableau Spot Remover

PROPAN-2-OL 10-30%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-

2119457558-25

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

ETHYL ACETATE 10-30%

CAS number: 141-78-6 EC number: 205-500-4 REACH registration number: 01-

2119475103-46

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R66 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air at once.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention

immediately.

Ingestion Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and

may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-

up.

5.3. Advice for firefighters

Tableau Spot Remover

Protective actions during firefighting

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours.

Warn firefighters that aerosols are involved.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate.

Avoid inhalation of vapours.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with

sand, earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Keep away from heat, sparks and open

flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent

material.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate

temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do

not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Long-term exposure limit (8-hour TWA): 1500 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm Short-term exposure limit (15-minute): WEL 400 ppm

Tableau Spot Remover

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

PROPAN-2-OL (CAS: 67-63-0)

DNEL Industry - Dermal; Long term systemic effects: 888 mg/kg/day

> Industry - Inhalation; Long term systemic effects: 500 mg/m³ Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Dermal; Long term systemic effects: 26 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m3

PNEC - Fresh water; 140.9 mg/l

> - Marine water; 140.9 mg/l - Intermittent release; 140.9 mg/l - Sediment (Freshwater); 552 mg/kg - Sediment (Marinewater); 552 mg/kg

- STP; 2251 mg/l - Soil; 28 mg/kg

8.2. Exposure controls

controls

Appropriate engineering

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any

occupational exposure limits for the product or ingredients.

Personal protection When using do not smoke.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant,

> impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can

provide information about the breakthrough time of the glove material.

Wash hands after handling. Wash hands at the end of each work shift and before eating, Hygiene measures

smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of

Clear.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Aerosol. **Appearance** Colour

Odour Organic solvents.

Flash point < -40°C

Upper/lower flammability or

explosive limits

Lower: 1.8% - Upper 9.5%

410-580°C **Auto-ignition temperature**

Comments Information given is applicable to the major ingredient.

9.2. Other information

Tableau Spot Remover

Other information Not available.

Volatile organic compound This product contains a maximum VOC content of 655 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable at normal ambient temperatures and when used as recommended.

10.2. Chemical stability

Stability Avoid the following conditions: Heat, sparks, flames.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Does not decompose when used and stored as recommended.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high

temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or

vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information Deliberately concentrating and inhaling the contents of this container is dangerous and can be

tatal.

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause

headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

Skin contact Irritating to skin.

Eye contact Irritating to eyes.

Acute and chronic health

hazards

Arrhythmia (deviation from normal heart beat). Irritating to skin. In high concentrations,

vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness

and nausea.

Route of entry Inhalation

Target organs Central nervous system Respiratory system, lungs

Medical symptoms Skin irritation. Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may

cause drowsiness and dizziness.

SECTION 12: Ecological Information

Tableau Spot Remover

Ecotoxicity This product has not been tested but contains ingredients which are toxic or very toxic to

aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent

contents entering watercourses.

12.1. Toxicity

Toxicity Not available.

12.2. Persistence and degradability

Persistence and degradability Not available.

12.3. Bioaccumulative potential

Bioaccumulative potential Not available.

12.4. Mobility in soil

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

Not available.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Do not puncture or incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated

because of the risk of an explosion.

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR

and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported

as Limited Quantities. Aerosols not so packed and labelled must show the following.

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

AEROSOLS

Tableau Spot Remover

Proper shipping name (IMDG) AEROSOLS (CONTAINS Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ADN packing group None

ICAO packing group None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

EU legislation Commission Regulation (EU) No 453/2010 of 20 May 2010.

Tableau Spot Remover

Guidance Workplace Exposure Limits EH40.

CHIP for everyone HSG228.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments Supplemental information added.

Revision date 05/07/2016

Revision 2

SDS number 10789

SDS status Approved.

Risk phrases in full R11 Highly flammable.

R12 Extremely flammable. R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H229 Pressurised container: may burst if heated

Hoop O . . :

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.