SAFETY DATA SHEET

according to Regulation (EC) No. 1272/2008

Tableau Leather Cream Ref 593/2

Version 2.0 Revision Date 24/3/20 Print Date 24/3/20

1. Identification of the substance/mixture and of the company/undertaking

Commercial name : Tableau Leather Cream

Product type : Wax Polish

Intended / Recommended Use : Wax for Leather Care

Manufacturer Name and address : RPM Marketing (Sussex) Tel +44 (0)1424 224620

PO Box 1

BEXHILL ON SEA email: info@tableauproducts.com

East Sussex <u>www.tableauprodu</u>cts.com

TN39 3ZQ England

Emergency telephone number: 01424 575131 Ext 3 Office Hours (Mon- Fri 9am-5pm) only.

2. Hazards identification

Signal Word Warning

Hazard Statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

Precautionary Statements

P271 Use only outdoors or in a well-ventilated area.

 ${\tt P280\ Wear\ protective\ gloves/protective\ clothing/eye\ protection/face\ protection}.$

P261 Avoid breathing vapour/spray.

P331 Do NOT induce vomiting.

In case of fire, use carbon dioxide (CO2) or dry chemical extinguisher. Do $\,$

not use water.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.





Composition/information on ingredients	Rango	EINECS	CAS	OEL	Classification
Name	Range			OEL	
HYDROCARBONS, C9 - C11, n-alkanes,	<25%	265-150-3	64742-48-9		Physical and Chemical Hazards Flam. Liq. 3
isoalkanes, cyclics, <2% aromatics.					H226
					Human health EUH066;STOT SE 3 - H336;A
					Tox. 1 - H304
					Environment Not classified.
Water	>70%		7732-18-5		Not classified as hazardous
Water	27070		7732-10-3		Not classified as flazardous
Blend of waxes	<20%				Not classified as hazardous
biend of waxes					
mixture of saturated and unsaturated fatty	<5%	204-007-1	112-80-1		Not classified as hazardous
acids					
Morpholine	<2%	203-815-1	110-91-8		H226 Flammable liquid and vapour.
					H302 Harmful if swallowed.
					H312 Harmful in contact with skin.
					H314 Causes severe skin burns and eye
					damage.
					·
Polydimethylsiloxane	<5%		63148-62-9		Not classified as hazardous
ALCOHOL ETHOM// ATE			50044.05.5		V 200 V 244
ALCOHOL ETHOXYLATE	<0.2		69011-36-5		Xn;R22. Xi;R41.
Amides, C16-18 and C18-unsatd	<0.2		68603-38-3		Xi;R38,R41.
	<0.2		00003-30-3		AI,N30,N41.
N,N-bis(hydroxyethyl)					

4. First aid measures

4.1. Description of first aid measures

General information

Remove victim immediately from source of exposure. Provide fresh air, warmth and rest, preferably in comfortable upright sitting position.

Perform artificial respiration if breathing has stopped. Do not give victim anything to drink if they are unconscious.

Inhalation

Remove victim immediately from source of exposure. Move into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Get medical attention if any discomfort continues.

Ingestion

Immediately rinse mouth and provide fresh air. DO NOT induce vomiting if swallowed chemical is dissolved in petroleum-based material.

Danger of aspiration and development of chemical pneumonia. Get medical attention immediately!

Skin contact

Remove contaminated clothes and rinse skin thoroughly with water. Rinse with water. Contact physician if discomfort continues.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Vapours may cause drowsiness and dizziness. Headache. Nausea, vomiting.

Ingestion

May cause discomfort if swallowed. Nausea, vomiting. Diarrhoea.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

Eye contact

Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Firefighting measures

5.1. Extinguishing media

Extinguishing media

Extinguish with foam, carbon dioxide or dry powder. Water spray, fog or mist.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

Specific hazards

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Aldehydes.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Keep up-wind to avoid fumes. If possible, fight fire from protected position. Move container from fire area if it can be done without risk. Use supplied air respirator if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control. Avoid water in straight hose stream; will scatter and spread fire. Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet. Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area. In case of inadequate ventilation, use respiratory protection. Take precautionary measures against static discharges. Do not smoke, use open fire or other sources of ignition. Do not breathe vapour. Eye contact MUST be prevented by means of suitable personal protection equipment.

6.2. Environmental precautions

Do not discharge onto the ground or into water courses. Do not allow ANY environmental contamination. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

If leakage cannot be stopped, evacuate area. Clean-up personnel should use respiratory and/or liquid contact protection. Wash thoroughly after dealing with a spillage. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Transfer to a container for disposal. Flush area with plenty of water.

6.4. Reference to other sections

For personal protection, see section 8

7. Handling and storage

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented. Storage tanks and other containers must be grounded. Protect electric equipment against sparking in case of risk of explosion. Wear full protective clothing for prolonged exposure and/or high concentrations. Contaminated rags and cloths must be put in fireproof containers for disposal. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Do not eat, drink or smoke when using the product. Container must be kept tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep away from food, drink and animal feeding stuffs. Avoid contact with oxidising agents. Flammable/combustible - Keep away from oxidisers, heat and flames. Ground container and transfer equipment to eliminate static electric sparks. Keep in original container. Store away from: Acids. Suitable containers: mild steel, stainless steel.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

8. Exposure controls/personal protection

NON HAZARDOUS INGREDIENTS

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment

Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use specified dust masks.

Hand protection

Use protective gloves made of:

Blue Nitrile, powder-free. Category 3.

Eye protection

Wear approved safety goggles.

Hygiene measures



9. Physical and chemical properties

Appearance : Off white liquid

Odour : Solvent
Flash point : >40°C

Ignition temperature:

Lower explosion limit:

Upper explosion limit:

Not Available

Upper explosion limit:

Not Available

Flammability (solid, gas):

Not Available

Oxidizing properties:

Autoignition temperature:

>230°C

pH: Not Available Melting point: Not Available

Boiling point : 130°C

Vapour pressure : Not Available Density : $\sim 0.8 \, \text{g/cm} 3$.

Water solubility: Insoluble in water Partition coefficient: n- octanol/water: Not Available Solubility in other solvents: Not Available Viscosity, dynamic: Not Available Viscosity, kinematic: Not Available Not Available Relative vapour density: Evaporation rate: Not Available Other information Oxidising potential: Not Available

10. Stability and reactivity Note: no data available

10.1. Reactivity

10.2. Chemical stability

No particular stability concerns.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising substances.

10.6. Hazardous decomposition products

11. Toxicological information

11.1. Information on toxicological effects

Inhalation

 $\label{eq:maycause} \mbox{May cause irritation to the respiratory system.}$

Ingestion

May cause internal injury. Gastrointestinal symptoms, including upset stomach.

Skin contact

Prolonged or repeated exposure may cause severe irritation.

Eye contact

May cause severe irritation to eyes.

Health Warnings

This product has low toxicity. Only large volumes may have adverse impact on human health.

12. Ecological information

Ecotoxicity

No data is available on the product itself

- 12.1. Toxicity
- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Results of PBT and vPvB assessment
- 12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

14. Transport information

14.1. UN number

UN No. (ADR/RID/ADN) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper Shipping Name Paint related material - Hydrocarbons, liquid, n.o.s.

14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR Label No. 3

IMDG Class 3

ICAO Class/Division 3

Transport Labels



14.4. Packing group

ADR/RID/ADN Packing group III

IMDG Packing group III

ICAO Packing group III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

110.

14.6. Special precautions for user

EMS F-E, S-D

Emergency Action Code 3Y

Hazard No. (ADR) 30

Tunnel Restriction Code (D/E)

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

National Regulations

Workplace Exposure Limits 2005 (EH40)

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

Water hazard classification

WGK

16. Other information Full text of R-phrases referred to under sections 2 and 3

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

Disclaimer:

The information contained in this data sheet is, to the best of our knowledge and belief, and is based upon our technical knowledge of the product and accurate the date of issue.

No warranty or representation, express or implied, is made as to its accuracy, reliability or completeness.

RPM Marketing (Sussex) will not be responsible for any damage or injury resulting from any inherent hazard of the material,

the abnormal use of the material or from failure to adhere to recommendation.