# SAFETY DATA SHEET
Tableau Anti Tarnish Lacquer 200ml Aerosols

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name** Tableau Anti Tarnish Lacquer 200ml Aerosols

**Product number** TAL

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Lacquer

### 1.3. Details of the supplier of the safety data sheet

**Supplier**

RPM Marketing (Sussex)
PO Box 1
BEXHILL ON SEA
East Sussex
TN39 3ZQ

Tel: 01424 224620

### 1.4. Emergency telephone number

**Emergency telephone** (01424 575131 Ext 4 Office Hours (Mon- Fri 9am-5pm) only.)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification (SI 2019 No. 720)**

**Physical hazards** Aerosol 1 - H222, H229

**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336

**Environmental hazards** Not Classified

**Human health** Vapours and spray/mists in high concentrations are narcotic. See Section 11 for additional information on health hazards.

**Environmental** The product is not expected to be hazardous to the environment.

**Physicochemical** Containers can burst violently or explode when heated, due to excessive pressure build-up. The product is extremely flammable. Vapours may form explosive mixtures with air.

### 2.2. Label elements

**Hazard pictograms**

**Signal word** Danger

**Hazard statements**

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

# Tableau Anti Tarnish Lacquer 200ml Aerosols

| | |
|---|---|
| **Precautionary statements** | P102 Keep out of reach of children.<br>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P211 Do not spray on an open flame or other ignition source.<br>P251 Do not pierce or burn, even after use.<br>P261 Avoid breathing vapour/ spray.<br>P271 Use only outdoors or in a well-ventilated area.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.<br>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.<br>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.<br>P312 Call a POISON CENTRE/doctor if you feel unwell.<br>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| **Supplemental label information** | EUH066 Repeated exposure may cause skin dryness or cracking. |
| **Contains** | ACETONE, 1-METHOXY-2-PROPANOL, 2-METHOXY-1-METHYLETHYL ACETATE |
| **Supplementary precautionary statements** | P264 Wash contaminated skin thoroughly after handling.<br>P337+P313 If eye irritation persists: Get medical advice/ attention.<br>P403+P233 Store in a well-ventilated place. Keep container tightly closed.<br>P405 Store locked up.<br>P501 Dispose of contents/ container in accordance with national regulations. |

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE** **10-30%**

CAS number: 68476-85-7 EC number: 270-704-2

**Classification**
Flam. Gas 1A - H220
Press. Gas (Comp.) - H280

**ACETONE** **10-30%**

CAS number: 67-64-1 EC number: 200-662-2

**Classification**
Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

**1-METHOXY-2-PROPANOL** **10-30%**

CAS number: 107-98-2 EC number: 203-539-1

**Classification**
Flam. Liq. 3 - H226
STOT SE 3 - H336

# Tableau Anti Tarnish Lacquer 200ml Aerosols

**XYLENE** **5-10%**

CAS number: 1330-20-7 EC number: 215-535-7

**Classification**
Flam. Liq. 3 - H226
Acute Tox. 4 - H312
Acute Tox. 4 - H332
Skin Irrit. 2 - H315
Eye Irrit. 2 - H319
STOT SE 3 - H335
STOT RE 2 - H373
Asp. Tox. 1 - H304
Aquatic Chronic 3 - H412

**2-METHOXY-1-METHYLETHYL ACETATE** **5-10%**

CAS number: 108-65-6 EC number: 203-603-9

**Classification**
Flam. Liq. 3 - H226
STOT SE 3 - H336

**N-BUTYL METHACRYLATE** **<1%**

CAS number: 97-88-1 EC number: 202-615-1

**Classification**
Flam. Liq. 3 - H226
Skin Irrit. 2 - H315
Eye Irrit. 2 - H319
Skin Sens. 1 - H317
STOT SE 3 - H335

**METHYL METHACRYLATE** **<1%**

CAS number: 80-62-6 EC number: 201-297-1

**Classification**
Flam. Liq. 2 - H225
Skin Irrit. 2 - H315
Skin Sens. 1 - H317
STOT SE 3 - H335

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**General information** Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If in doubt, get medical attention promptly.

# Tableau Anti Tarnish Lacquer 200ml Aerosols

**Ingestion** Rinse mouth thoroughly with water. Remove person to fresh air and keep comfortable for breathing. Get medical attention.

**Skin contact** Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.

**Eye contact** Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

**Protection of first aiders** First aid personnel should wear appropriate protective equipment during any rescue.

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** See Section 11 for additional information on health hazards.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Foam, carbon dioxide or dry powder.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Use water to keep fire exposed containers cool and disperse vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Use suitable respiratory protection if ventilation is inadequate.

# Tableau Anti Tarnish Lacquer 200ml Aerosols

**Advice on general occupational hygiene** Wash promptly with soap and water if skin becomes contaminated. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Protect from freezing and direct sunlight. Store in a dry place. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

#### Occupational exposure limits

**PETROLEUM GASES, LIQUEFIED <0.1% 1,3-BUTADIENE**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³
Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³
Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³
Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

**ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³
Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³
Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³
Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

**1-METHOXY-2-PROPANOL**

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³
Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m³
Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³
Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m³
Sk, Sk

**XYLENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³
Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³
Sk, Sk

**2-METHOXY-1-METHYLETHYL ACETATE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m³
Sk

**METHYL METHACRYLATE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³
Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

WEL = Workplace Exposure Limit.
Sk = Can be absorbed through the skin.

**ACETONE (CAS: 67-64-1)**

# Tableau Anti Tarnish Lacquer 200ml Aerosols

**DNEL**

Workers - Dermal; Long term systemic effects: 186 mg/kg/day
Workers - Inhalation; Short term local effects: 2420 mg/m³
Workers - Inhalation; Long term systemic effects: 1210 mg/m³

**PNEC**

- Sediment (Freshwater); 30.4 mg/kg
- Sediment (Marinewater); 3.04 mg/kg
- marine water; 1.06 mg/l
- Soil; 29.5 mg/kg

### 1-METHOXY-2-PROPANOL (CAS: 107-98-2)

**DNEL**

Consumer - Oral; Long term systemic effects: 33 mg/kg/day
Workers - Dermal; Long term systemic effects: 183 mg/kg/day
Consumer - Dermal; Long term systemic effects: 78 mg/kg/day
Workers - Inhalation; Short term systemic effects: 553.5 mg/m³
Workers - Inhalation; Short term local effects: 553.5 mg/m³
Workers - Inhalation; Long term systemic effects: 369 mg/m³
Consumer - Inhalation; Long term systemic effects: 43.9 mg/m³

**PNEC**

- Fresh water; 10 mg/l
- marine water; 1 mg/l
- Intermittent release; 100 mg/l
- Sediment (Freshwater); 52.3 mg/kg
- Sediment (Marinewater); 5.2 mg/kg
- Soil; 4.59 mg/kg
- STP; 100 mg/l

### XYLENE (CAS: 1330-20-7)

**DNEL**

Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
Workers - Dermal; Long term systemic effects: 180 mg/kg/day
Consumer - Inhalation; Short term local effects: 174 mg/m³
Consumer - Inhalation; Short term systemic effects: 174 mg/m³
Workers - Inhalation; Short term systemic effects: 289 mg/m³
Workers - Inhalation; Short term local effects: 289 mg/m³
Consumer - Inhalation; Long term systemic effects: 14.8 mg/m³
Workers - Inhalation; Long term systemic effects: 77 mg/m³

**PNEC**

- Fresh water; 0.327 mg/l
- marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

### 2-METHOXY-1-METHYLETHYL ACETATE (CAS: 108-65-6)

**DNEL**

Industry - Dermal; Long term systemic effects: 153.5 mg/kg/day
Industry - Inhalation; Long term systemic effects: 275 mg/m³
Consumer - Dermal; Long term systemic effects: 54.8 mg/kg/day
Consumer - Inhalation; Long term systemic effects: 33 mg/m³
Consumer - Oral; Long term systemic effects: 1.67 mg/kg/day

# Tableau Anti Tarnish Lacquer 200ml Aerosols

| | |
|---|---|
| **PNEC** | Industry - Fresh water; Long term 0.635 mg/l<br>Industry - marine water; Long term 0.0635 mg/l<br>Industry - Fresh water; Long term 3.29 mg/kg<br>Industry - Sediment (Freshwater); Long term 3.29 mg/kg<br>Industry - Sediment (Marinewater); Long term 0.329 mg/kg<br>Industry - Soil; Long term 0.29 mg/kg<br>Industry - STP; Long term 100 mg/l |

## 8.2. Exposure controls

| | |
|---|---|
| **Eye/face protection** | Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. |
| **Hand protection** | No specific requirements are anticipated under normal conditions of use. |
| **Other skin and body protection** | Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. |
| **Respiratory protection** | No specific recommendations. If ventilation is inadequate, suitable respiratory protection must be worn. |

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

| | |
|---|---|
| **Appearance** | Aerosol. |
| **Colour** | Clear. |
| **Odour** | Solvents |
| **Odour threshold** | No information available. |
| **pH** | No information available. |
| **Melting point** | No information available. |
| **Initial boiling point and range** | -41°C |
| **Flash point** | < -40°C Closed cup. |
| **Evaporation rate** | No information available. |
| **Evaporation factor** | No information available. |
| **Flammability (solid, gas)** | No information available. |
| **Upper/lower flammability or explosive limits** | Lower flammable/explosive limit: 0.8 % Upper flammable/explosive limit: 13.1 % |
| **Vapour pressure** | No information available. |
| **Vapour density** | No information available. |
| **Relative density** | 0.735 |
| **Solubility(ies)** | Insoluble in water. |
| **Partition coefficient** | No information available. |
| **Auto-ignition temperature** | 270°C |
| **Decomposition Temperature** | No information available. |
| **Viscosity** | No information available. |
| **Explosive properties** | No information available. |

# Tableau Anti Tarnish Lacquer 200ml Aerosols

**Oxidising properties** No information available.

### 9.2. Other information

**Other information** None.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** No test data specifically related to reactivity available for this product or its ingredients.

### 10.2. Chemical stability

**Stability** The product may not be stable under some conditions of storage or use.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None known.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

### 10.5. Incompatible materials

**Materials to avoid** None known.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** None at ambient temperatures.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Acute toxicity - dermal**

**ATE dermal (mg/kg)** 11,111.11

**Acute toxicity - inhalation**

**ATE inhalation (vapours mg/l)** 111.11

**Inhalation** May cause drowsiness or dizziness. Vapours in high concentrations are narcotic. Vapours may cause headache, fatigue, dizziness and nausea.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Eye contact** Causes serious eye irritation.

**Acute and chronic health hazards** No specific long-term effects known.

**Route of exposure** Inhalation Skin and/or eye contact

**Toxicological information on ingredients.**

**ACETONE**

**Acute toxicity - oral**

**Acute toxicity oral ($LD_{50}$ mg/kg)** 5,800.0

**Species** Rat

# Tableau Anti Tarnish Lacquer 200ml Aerosols

| | |
|---|---|
| **ATE oral (mg/kg)** | 5,800.0 |
| **Acute toxicity - dermal** | |
| **Acute toxicity dermal ($LD_{50}$ mg/kg)** | 7,800.0 |
| **Species** | Rabbit |
| **ATE dermal (mg/kg)** | 7,800.0 |
| **Acute toxicity - inhalation** | |
| **Acute toxicity inhalation ($LC_{50}$ vapours mg/l)** | 21.0 |
| **Species** | Rat |
| **ATE inhalation (vapours mg/l)** | 21.0 |

**1-METHOXY-2-PROPANOL**

| | |
|---|---|
| **Acute toxicity - oral** | |
| **Acute toxicity oral ($LD_{50}$ mg/kg)** | 5,660.0 |
| **Species** | Rat |
| **ATE oral (mg/kg)** | 5,660.0 |
| **Acute toxicity - dermal** | |
| **Acute toxicity dermal ($LD_{50}$ mg/kg)** | 13,000.0 |
| **Species** | Rabbit |
| **ATE dermal (mg/kg)** | 13,000.0 |
| **Acute toxicity - inhalation** | |
| **Acute toxicity inhalation ($LC_{50}$ vapours mg/l)** | 54.6 |
| **Species** | Rat |
| **ATE inhalation (vapours mg/l)** | 54.6 |

**XYLENE**

| | |
|---|---|
| **Acute toxicity - oral** | |
| **Acute toxicity oral ($LD_{50}$ mg/kg)** | 4,300.0 |
| **Species** | Rat |
| **ATE oral (mg/kg)** | 4,300.0 |
| **Acute toxicity - dermal** | |
| **Acute toxicity dermal ($LD_{50}$ mg/kg)** | 3,200.0 |

# Tableau Anti Tarnish Lacquer 200ml Aerosols

| | |
|---|---|
| **Species** | Rabbit |
| **ATE dermal (mg/kg)** | 1,100.0 |
| **Acute toxicity - inhalation** | |
| **ATE inhalation (vapours mg/l)** | 11.0 |

**2-METHOXY-1-METHYLETHYL ACETATE**

| | |
|---|---|
| **Acute toxicity - oral** | |
| **Acute toxicity oral ($LD_{50}$ mg/kg)** | 8,532.0 |
| **Species** | Rat |
| **ATE oral (mg/kg)** | 8,532.0 |
| **Acute toxicity - dermal** | |
| **Acute toxicity dermal ($LD_{50}$ mg/kg)** | 5,001.0 |
| **Species** | Rat |
| **ATE dermal (mg/kg)** | 5,001.0 |
| **Acute toxicity - inhalation** | |
| **Acute toxicity inhalation ($LC_{50}$ vapours mg/l)** | 23.8 |
| **Species** | Rat |
| **ATE inhalation (vapours mg/l)** | 23.8 |

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecological information on ingredients.**

**ACETONE**

| | |
|---|---|
| **Acute aquatic toxicity** | |
| **Acute toxicity - fish** | $EC_{50}$, 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill) |
| **Acute toxicity - aquatic invertebrates** | $EC_{50}$, : 8800 mg/l, Daphnia magna |

**1-METHOXY-2-PROPANOL**

| | |
|---|---|
| **Acute aquatic toxicity** | |
| **Acute toxicity - fish** | $LC_{50}$, 96 hours: 6812 mg/l, Leuciscus idus (Golden orfe)<br>$LC_{50}$, 96 hours: 20800 mg/l, Pimephales promelas (Fat-head Minnow) |
| **Acute toxicity - aquatic invertebrates** | $LC_{50}$, 48 hours: >500 mg/l, Daphnia magna |
| **Acute toxicity - aquatic plants** | $EC_{50}$, : 1001 mg/l, Selenastrum capricornutum |

# Tableau Anti Tarnish Lacquer 200ml Aerosols

**XYLENE**

**Acute aquatic toxicity**

| | |
|---|---|
| **Acute toxicity - fish** | LOEC, : >1 - <10 mg/l, Fish |
| **Acute toxicity - aquatic plants** | LOEC, : >1 - <10 mg/l, Algae |

**2-METHOXY-1-METHYLETHYL ACETATE**

**Acute aquatic toxicity**

| | |
|---|---|
| **Acute toxicity - fish** | $LC_{50}$, 96 hours: 180 mg/l, Oncorhynchus mykiss (Rainbow trout) |
| **Acute toxicity - aquatic invertebrates** | $EC_{50}$, 48 hours: >500 mg/l, Daphnia magna |
| **Acute toxicity - aquatic plants** | $EC_{50}$, 96 hours: >1000 mg/l, Selenastrum capricornutum |

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Partition coefficient** No information available.

### 12.4. Mobility in soil

**Mobility** No data available.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Dispose of waste product or used containers in accordance with local regulations Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

**Disposal methods** Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not pierce or burn, even after use.

**Waste class** The waste code classification is to be carried out according to the European Waste Catalogue (EWC).

## SECTION 14: Transport information

### 14.1. UN number

**UN No. (ADR/RID)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

**UN No. (ADN)** 1950

# Tableau Anti Tarnish Lacquer 200ml Aerosols

## 14.2. UN proper shipping name

| | |
|---|---|
| **Proper shipping name (ADR/RID)** | AEROSOLS, FLAMMABLE |
| **Proper shipping name (IMDG)** | AEROSOLS, FLAMMABLE |
| **Proper shipping name (ICAO)** | AEROSOLS, FLAMMABLE |
| **Proper shipping name (ADN)** | AEROSOLS, FLAMMABLE |

## 14.3. Transport hazard class(es)

| | |
|---|---|
| **ADR/RID class** | 2.1 |
| **ADR/RID classification code** | 5F |
| **ADR/RID label** | 2.1 |
| **IMDG class** | 2.1 |
| **ICAO class/division** | 2.1 |
| **ADN class** | 2.1 |

**Transport labels**

## 14.4. Packing group

Not applicable.

## 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

## 14.6. Special precautions for user

| | |
|---|---|
| **EmS** | F-D, S-U |
| **ADR transport category** | 2 |
| **Tunnel restriction code** | (D) |

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

| | |
|---|---|
| **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** | Not applicable. |

# SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations**

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019 (as amended).
The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 (SI 2020 No. 1577) (as amended).
Control of Substances Hazardous to Health Regulations 2002 (as amended).
EH40/2005 Workplace exposure limits.

## 15.2. Chemical safety assessment

# Tableau Anti Tarnish Lacquer 200ml Aerosols

No chemical safety assessment has been carried out.

## SECTION 16: Other information

| | |
|---|---|
| **Revision date** | 17/10/2022 |
| **Revision** | 2 |
| **Supersedes date** | 17/10/2022 |
| **SDS number** | 8903 |
| **Hazard statements in full** | H220 Extremely flammable gas.<br>H222 Extremely flammable aerosol.<br>H225 Highly flammable liquid and vapour.<br>H226 Flammable liquid and vapour.<br>H229 Pressurised container: may burst if heated.<br>H280 Contains gas under pressure; may explode if heated.<br>H304 May be fatal if swallowed and enters airways.<br>H312 Harmful in contact with skin.<br>H315 Causes skin irritation.<br>H317 May cause an allergic skin reaction.<br>H319 Causes serious eye irritation.<br>H332 Harmful if inhaled.<br>H335 May cause respiratory irritation.<br>H336 May cause drowsiness or dizziness.<br>H373 May cause damage to organs through prolonged or repeated exposure.<br>H412 Harmful to aquatic life with long lasting effects. |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability of such information for their own particular use.