Page 1 of 7 Issued: 19/04/2015; Revision No.1 Regulation (EU) No. 453/2010

### 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

- 1.1 Product Identifier Material name : Foam Leather Cleaner Aerosol
- **1.2** Relevant identified uses of the substance or mixture and uses advised against Product use : Foaming Cleanser
- 1.3 Details of the supplier of the safety data sheet

Supplier	RPM Marketing (Sussex)
	PO Box 1
	Bexhill on Sea
	East Sussex
	TN39 3ZQ

Tel 01424 224620

1.4 Emergency Tel 01424 464809 Mon- Fri 10am – 4pm Excl. 1pm-2pm) Quote Code TLCM

## 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

According to 1272/2008/EC: Classification, Labelling and Packaging of Substances and Mixtures (CLP) Regulation:

Extremely Flammable Aerosol Category 1 Skin Irritant Category 2 Eye Irritant Category 2

#### 2.2 Label elements

Labelling according to EC Directives: 1272/2008/EC:

Signal word: Danger



Pictogram(s):

H-Statements:	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
P-Statements:	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.

## 2.2 Label elements (continued)

P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.
P280	Wear protective gloves/eye/face protection.
P302+P352	IF ON SKIN: Wash with soap and water.
P305+P351+P3	338 IF IN EYES, rinse cautiously with water for several minutes. Remove contact lenses if
	present and easy to do - continue rinsing.
P337+P313	It eye irritation persists, get medical advice/attention.
P261	Avoid breathing vapour/spray.
P271	Use only outdoors or in a well-ventilated area.

## **2.3 Other hazards** In use, may form flammable / explosive vapour-air mixture.

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2 Mixtures:

#### Hazardous components

Chemical Name	CAS No./ EC No./ Reg. No	Classification (1272/2008/EC)	Content
ALCOHOLS, C10-12 ETHOXYLATED (5EO)	67254-71- 1 - -	Eye Dam.1; H318	0-1%
SODIUM XYLENE SULPHONATE	1300-72-7 215-090-9 -	Eye Irrit.2; H319	0-1%
TETRAPOTASSIUM PYROPHOSPHATE	7320-34-5 230-785-7 -	Eye Irrit.2; H319	0-1%
RTQRCP/4/QN	"89/85/2 222/883/9 23/433; 67977: /47/	Hrco 0Ns 04=J 447 G{g"Ktk04=J 53; SVQV"UG5=J 558	0-3%
LIQUEFIED PETROLEUM GAS (contains <0.1% 1,3-butadiene)	68476-85-7 270-704-2 -	Flam.Gas 1; H220 Gas under pressure; H280	10-30%

See Section 16 for the full text of the H-statements noted above.

## 4. FIRST AID MEASURES

## 4.1 Description of first aid measures

**General advice:** Remove casualty from exposure ensuring one's own safety whilst doing so. Take off any contaminated clothing and shoes/boots immediately. Never give anything by mouth to an unconscious person.

Skin contact: Wash with soap and water. Seek medical advice if irritation develops.

Eye contact: Rinse with water for 10 minutes and seek medical advice if irritation persists.

Ingestion: Rinse mouth with water and give water to drink. Do not induce vomiting. Seek medical advice.

Inhalation: Remove to fresh air. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed: May cause irritation to skin and eyes with prolonged contact.

4.3 Indication of any immediate medical attention and special treatment needed: See skin and eye contact information above.

## **5. FIRE-FIGHTING MEASURES**

## 5.1 Extinguishing media

Suitable extinguishing media:	Carbon dioxide; dry chemical powder; alcohol or polymer foam.
Unsuitable extinguishing media:	High volume water jet
5.2 Special hazards arising from	the substance or mixture

Specific hazards during fire-fighting:	Irritating/toxic fumes may be released at elevated temperatures.
5.3 Advice for fire-fighters:	
Special protective equipment: Further information:	Wear self-contained breathing apparatus. Use personal protective equipment. Standard procedure for chemical fires. Use water spray to cool containers.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Use personal protective equipment to deal with spillage.

Do not allow fire run-off to enter drains.

#### **6.2** Environmental precautions

Contain the spillage using sufficient appropriate absorbent material. Do not discharge into drains or rivers, but if contamination to waterways has occurred, inform local authorities.

## 6.3 Methods and materials for containment and cleaning up

Wipe up liquid spillage with absorbent material such as sand, earth, or vermiculite, and place in a labelled container for disposal in accordance with local/national regulations.

6.4 References to other sections: See sections 8 and 13 for personal protection and disposal information.

## 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Do not breathe spray mist. Avoid contact with skin and eyes. Handle with care.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, well ventilated area, below 50°C. Protect from frost, heat and sunlight. Keep away from food, drink and animal feed.

7.3 Specific end use(s): No information available.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## **8.1** Control parameters

Chemical name	8hr TWA	15min STEL	Referenc
Propan-2-ol	999 mg/m <sup>3</sup> /400 ppm	1250 mg/m <sup>3</sup> /500 ppm	EH40/2005
Liquefied petroleum gas	1750 mg/m <sup>3</sup> /1000ppm	2810 mg/m <sup>3</sup> /1250 ppm	EH40/2005

### 8.2 Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

### Personal protective equipment

Respiratory protection: Unlikely to be necessary in normal circumstances.

**Hand protection**: Wear chemically resistant gloves such as butyl rubber approved to standard EN 374; material thickness 0.5mm; break through time  $\geq$  480 min. Gloves must be replaced after 8 hours of wear. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Check with glove manufacturer for specific advice.

**Eye protection**: Chemical splash goggles if eye contact is reasonably probable. The selected goggles or glasses must satisfy the European standard EN 166.

Skin and body protection: General workwear.

**Hygiene measures:** Handle in accordance with good industrial hygiene and safety practices. Do not eat or drink whilst using the product. Wash hands before breaks and at the end of the work day. Wash contaminated clothing before re-use.

Environmental exposure controls: Do not discharge into drains or rivers.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

State and colour	Aerosol emitting foamy white spray.
Odour	Mild
Odour Threshold	No data available
Flammability	Extremely flammable
Flash point	<0°C
Lower explosion limit	0.8%
Upper explosion limit	12.0%
Explosive properties	Not explosive
Thermal decomposition	No data available
Auto-ignition temperature	>230°C
Oxidising properties	Non-oxidising
Solubility in water	Soluble
Solubility in other solvents	Alcohols.
рН	10.0-11.0
Melting point/range	No data available
Boiling point/range	No data available
Relative density	No data available
Vapour pressure	No data available
Vapour density	No data available
Partition coefficient: n-octanol/water	No data available
Viscosity (kinematic)	No data available
Evaporation rate	No data available

#### 9.2 Other information

None

## **10. STABILITY AND REACTIVITY**

10.1 ReactivityGenerally non-reactive.10.2 Chemical stabilityStable under normal conditions.10.3 Possibility of hazardous reactionsNone if stored and used as directed.10.4 Conditions to avoidNone known.10.5 Incompatible materialsAcids. Oxidising agents.10.6 Hazardous decomposition productsOxides of carbon.

## **11. TOXICOLOGICAL INFORMATION**

## **11.1 Information on toxicological effects** Acute toxicity

Chemical name	Oral (LD50)	Inhalation (LC50)	Dermal (LD50)
Propan-2-ol	>2000 mg/kg (Rat)	No data available	>2000 mg/kg (Rabbit)
Liquefied petroleum gas	Not applicable	>20mg/l (Rat) 4h	Not applicable

Skin corrosion/irritation:	May be irritating with prolonged exposure.
Serious eye damage/eye irritation:	May be irritating.
Respiratory or skin sensitisation:	Not expected to be a sensitiser.
Repeated dose toxicity:	Repeated skin contact can cause defatting leading to dermatitis.
Carcinogenicity:	Not expected to be carcinogenic.
Mutagenicity:	Not expected to be mutagenic.
Toxicity for reproduction:	Not expected to be a hazard.
Specific target organ toxicity (STOT):	No data available.

### **Further information**

The product as a whole may cause irritation of skin, eyes, nose and upper respiratory tract if exposed to high levels of spray mist. May cause drowsiness or dizziness.

## **12. ECOLOGICAL INFORMATION**

## 12.1 Toxicity

Chemical name	Species	Test	Value
Propan-2-ol	Daphnia	EC50 48h	>100 mg/l
	Golden ide	LC50 48h	>100 mg/l
	Algae	EC50 72h	>100 mg/l

12.2 Persistence and degradability

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.5 Results of PBT and vPvB assessment 12.6 Other adverse effects Expected to be readily biodegradable. Low bioaccumulation potential. Soluble in water. Contains no PBT or vPvB substances. None expected.

## **13. DISPOSAL CONSIDERATIONS**

## 13.1 Waste treatment methods

Disposal operations: Dispose of in accordance with local and national regulations. Contact licensed waste disposal company. Most aerosols can be recycled. Do not pierce or burn or use a cutting torch on the empty aerosol container.

## **14. TRANSPORT INFORMATION**

General Information: The UN number for all aerosols is 1950. Aerosols packed in fibreboard cartons up to 30 kg gross weight, or shrink/stretch wrapped onto trays up to 20 kg gross weight may be transported as Limited Quantities, and should display the following symbol on the pack:



The following information relates to all other aerosols not transported as Limited Quantities:

14.1 UN number	ADR/RID/ADN; IMDG; ICAO	1950	
14.2 UN proper shipping name	AEROSOLS		
14.3 Transport hazard class(es)	ADR/RID/ADN Class	2, 5F	
	ADR/RID/ADN Class	Class 2, Gases	
	ADR Label No.	2.1	
	IMDG Class	2	
	ICAO Class/Division	2	
	ICAO Subsidiary risk	2.1	
	FLAMMABL	CAS	
	Transport labels		
14 4 Dealing Crown		Not applicable for corose	la
14.4 Packing Group	ADR/RID/ADN; IMDG; ICAO	Not applicable for aeroso	15
14.5 Environment hazards	Marine Pollutant	Not applicable for aeroso	ls.
14.6 Special precautions for user	· EMS	F-D, S-U	
<b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b> Not applicable for aerosols.			

## **15. REGULATORY INFORMATION**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **UK Regulatory References**

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2001 No.2677) with amendments.

### **EU Directives**

Regulations (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

### **Statutory Instruments**

The Chemicals (Hazard information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

### **Guidance Notes**

Health and Safety Executive Workplace Exposure Limits EH40.

### **15.2 Chemical Safety Assessment**

A Chemical Safety Assessment has not been performed on this product.

## **16. OTHER INFORMATION**

This safety data sheet is prepared in accordance with Commission Regulation (EU) No.453/2010.

### Full text of H-statements referred to under sections 2 and 3

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H314 Cause severe skin burns and eye damage.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

#### Abbreviations and acronyms

- CAS: Chemical Abstract Service (division of the American Chemical Society). {Section 3}.
- STOT: Single Target Organ Toxicity (Section 2; 11).
- SE: Single exposure (Section 2)
- TWA: Time-weighted average. (Section 8).
- STEL: Short-term exposure limit. (Section 8).
- PBT: Persistent, Bioaccumulative, Toxic. (Section 12).
- vPvB: very Persistent and very Bioaccumulative. (Section 12).

**Legal disclaimer**: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]